

Economical Pressure Switches

"SANMUR" manufactures economy pressure switches in the Series - SC, covering the following:

1) Pressure switches with fixed and variable differentials (Range covers from 0.1 to 32 Kg/cm2)

Pressure switches are electro-mechanical devices that sense changes in pressure by means of snap action electrical contacts at pre- set values of pressure.

These pressure switches can energise an alarm or control the process directly.

Since pressure switches are safety cut-outs they can ensure that high capital-cost equipments are saved by the actuation of the switch to set off an alarm or control equipments directly also through electrical linkage.


The economy model is ideal for a wide range of applications where high quality & reliability are required. It also provides the flexibility required for most industrial applications. Superior 5A / 15A contacts allows direct control of a motor or pump without the use of external relays - a true time and money saving proposal. Unique features include a convenient indicating scale for quick, open case and easy field adjustments. The rugged construction incorporates an exclusive SS 316 diaphragm pressure element for all ranges for exceptional compatibility, high accuracy & long service life. A spindle lock plate provides effective tamper proofing.

The compact size, elegant design and cost benefit make the "SANMUR" SC series switches a preferred choice.

Technical Data

Range	0.1 to 32 Kg/cm2
Sensing Element	SS 316 Diaphragm
Process Connection	1/4" BSP(F)
Enclosure	Powder coated Mild Steel case with ABS cover
Enclosure Protection	IP:32
Switch Type	1 SPDT
Switch Rating	5A / 15A , 250V AC
Cable Entry	Rubber Grommet
Mounting	Surface / Panel / Direct

Ordering Code





SANMUR CONTROLS PVT. LTD.

An ISO 9001: 2008 Certified Company

Series

al

Range Code

SCF	: Fixed differential
SCA	: Adjustable Differentia

Micro Switch

05	: 5A 250V AC
15	: 15A 250V AC

101	0.1 - 1.1	
105	0.1 - 1.5	
002	0.2 - 2.0	
004	0-4	
006	0.6 - 6.0	
010	0.5 - 10	
016	1 - 16	
025	2 - 25	
032	2 - 32	

Fixed Differential Chart(For SCF Series)				
Range Code	MSW		MWP	
	5A	15A		
101	0.1	0.2	6	
105	0.15	0.2	6	
002	0.15	0.2	6	
004	0.4	0.5	10	
006	0.5	0.6	10	
010	0.6	0.8	16	
016	1.0	1.2	25	
025	1.5	2.5	30	
032	2	3.5	35	


Adjustable Differential Chart(For SCA Series)			
Range Code	MSW		
	5A	15A	
101	0.1 - 0.2	0.1 - 0.4	
105	0.12 - 0.2	0.15 - 0.5	
002	0.12 - 0.2	0.15 - 0.5	
004	0.3 - 0.7	0.4 - 1.5	
006	0.3 - 0.7	0.5 - 2	
010	0.7 - 1.8	1.2 - 4	
016	0.9 - 1.8	1.5 - 5	
025	1.8 - 4	3 - 8	
032	2 - 4	4 - 9	

Spindle Lock Plate

ŝ

- Mounting Holes Ø4.5(2Nos.)

SANMUR R



Registered Office & Works:

SANMUR CONTROLS PVT. LTD.

1/A, Rajiv Gandhi Nagar I.E. (Extn) Kukatpally Balanagar Post, Hyderabad - 500 037 Tel/Fax: +91-40-2307 3406, 4210 2425 Email: sanmur@sanmur.com kcmohan16_hyd@dataone.in Website: www.sanmur.com

Distributor / Dealer / Agent

Process Connection (1/4" BSPF)

П